



Helping to protect lives globally

Jo**Bird**[®]

BUILT BY **THE BEST** TO
WITHSTAND **THE WORST.**

Product **data sheet**

JB06 Fire Hose cabinet



Typical use:

For the storage of 1 x 15-18M fire hose and nozzle. Designed for the offshore energy and commercial shipping sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access even when wearing gloves.

Standard specification:

Dimensions (mm)

Height x width x depth: 625 x 528 x 240

Aperture: 463H x 330W

Internal depth: 199

Weight Kg: 7Kg

Material specification:

Colour: Red RAL 3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: Graphite nylon

Handle: Nylon

Seal: EPDM

Optional Extras:

Other RAL colours

316 Stainless steel hinges

Class 1 fire retardant composites

Perspex window with bezel

IMO approved signage



Manufactured in the UK

